

# VIBE P LED

## Downlights



R60



R80





**DESCRIPTION:** Recessed mounted LED downlight  
**Light distribution type:** direct  
**Optical system:** faceted aluminium reflector, 60° / matt aluminium reflector, 80°, opal PMMA diffuser, low glare  
**Housing:** aluminium  
**Colour:** white, RAL9016

**GENERAL DATA:** Mains voltage: 220-240V, 50-60Hz  
 LED lifetime, h: 50000/L80B10  
 SDCM: 5  
 Protection class IEC: II  
 Ingress protection code: IP44  
 Mechanical impact resistance: IK04  
 Operating temperature range, °C: ta 0...+35

**INSTALLATION:** In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm<sup>2</sup>

**ENVIRONMENT:** Indoor

**APPLICATION:** Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place



PRODUCT	DIAMETER, mm	HEIGHT, mm	CUT-OUT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
VIBE P LED1x950 J721 T830/40/57 R60	114	66	95	950	10,0	95	80+	3000/4000/5700	0,3
VIBE P LED1x1900 G986 T830/40/57 R60	174	87	147	1900	20,0	95	80+	3000/4000/5700	0,4
VIBE P LED1x2550 G987 T830/40/57 R60	232	110	200	2660	28,0	95	80+	3000/4000/5700	0,7
VIBE P LED1x3350 J722 T830/40/57 R60	232	110	200	3325	35,0	95	80+	3000/4000/5700	0,7
VIBE P LED1x1100 J723 T830/40/57 R80	114	66	95	1100	10,0	110	80+	3000/4000/5700	0,3
VIBE P LED1x2400 G986 T830/40/57 R80	174	87	147	2400	20,0	120	80+	3000/4000/5700	0,4
VIBE P LED1x3350 G987 T830/40/57 R80	232	110	200	3320	27,9	119	80+	3000/4000/5700	0,7
VIBE P LED1x4050 J724 T830/40/57 R80	232	110	200	4025	35,0	115	80+	3000/4000/5700	0,7

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. The manufacturer is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

### AVAILABLE ACCESSORIES:



**Product:** VIBE P LED 20W G986 steel cover white  
**Description:** Surface mounting cover for VIBE P LED, white steel, 182x182x155mm\*

**Product:** VIBE P LED 28W G987 steel cover white  
**Description:** Surface mounting cover for VIBE P LED, white steel, 240x240x180mm\*

\*note - Luminaire with surface mounting cover, protection degree is IP20



**Product:** VIBE P LED 20W G986 steel cover black  
**Description:** Surface mounting cover for VIBE P LED, black steel, 182x182x155mm\*

**Product:** VIBE P LED 28W G987 steel cover black  
**Description:** Surface mounting cover for VIBE P LED, black steel, 240x240x180mm\*

\*note - Luminaire with surface mounting cover, protection degree is IP20

## OPTIONS AVAILABLE ON REQUEST:

CONTROL GEAR	EMERGENCY	CONNECTION	OTHER
DALI	EM3A	WIE3-0.5m	RND BLACK
	EM3D	WIE5D-0.5m	SQ WHITE
		QBX2-0.1m	SQ BLACK
		Europlug-1.5m	GLASS WHITE
		Europlug-3.0m	GLASS BLACK

## LUMINAIRE FRAME OPTIONS:



**Option:** RND BLACK

**Description:** Round luminaire frame in black, with dropped down glass cover



**Options:** SQ WHITE / SQ BLACK

**Description:** Square luminaire frame in white / black



**Option:** GLASS WHITE

**Description:** Round luminaire frame in white, with dropped down glass cover



**Option:** GLASS BLACK

**Description:** Round luminaire frame in black, with dropped down glass cover

R60

R80

